

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B66B 11/06		A1	(11) International Publication Number: WO 99/43599									
			(43) International Publication Date: 2 September 1999 (02.09.99)									
<p>(21) International Application Number: PCT/US99/03650</p> <p>(22) International Filing Date: 19 February 1999 (19.02.99)</p> <p>(30) Priority Data:</p> <table border="0"> <tr> <td>09/031,108</td> <td>26 February 1998 (26.02.98)</td> <td>US</td> </tr> <tr> <td>09/163,676</td> <td>30 September 1998 (30.09.98)</td> <td>US</td> </tr> <tr> <td>09/218,990</td> <td>22 December 1998 (22.12.98)</td> <td>US</td> </tr> </table> <p>(71) Applicant: OTIS ELEVATOR COMPANY [US/US]; 10 Farm Springs, Farmington, CT 06032 (US).</p> <p>(72) Inventors: JONES, David, Wayne; 2 San Antonio Court, Mentone (AU). KANZAKI, Yuji; 2-6-5-302, Nishi-jkuta, Tama-ku, Kawasaki-shi, Kanagawa-ken (JP). NABETANI, Tadaaki; 840-5-101, Oshitate, Inagi-shi, Tokyo (JP). MORI, Toshimitsu; 167-2, Hane Hadano-shi, Kanagawa (JP). SHIBASAKI, Shusaku; 1407-73, Ohse, Yasio Shi, Saitama Pref. 340-0822 (JP). SHIODA, Yasuhisa; 5-10-29, Minamiaoyama, Minato-ku, Tokyo (JP). TATENO, Hiroaki; 3-15-8-302, Seki Tama-ku, Kawasaki-shi, Kanagawa (JP).</p> <p>(74) Agent: HENLEY, Randy; Otis Elevator Company, Intellectual Property Dept., 10 Farm Springs, Farmington, CT 06032 (US).</p>			09/031,108	26 February 1998 (26.02.98)	US	09/163,676	30 September 1998 (30.09.98)	US	09/218,990	22 December 1998 (22.12.98)	US	<p>(81) Designated States: BR, CN, IN, JP, KR, RU, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published</p> <p><i>With international search report.</i></p> <p><i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
09/031,108	26 February 1998 (26.02.98)	US										
09/163,676	30 September 1998 (30.09.98)	US										
09/218,990	22 December 1998 (22.12.98)	US										
<p>(54) Title: DRUM DRIVE ELEVATOR USING FLAT BELT</p> <p>(57) Abstract</p> <p>An elevator system (10) includes an elevator car (18) supported for vertical movement on a belt (16) having an end fixed to the hoistway (26) and the other end wound about a drum (32) of a drum drive (12). When the belt (16) is wound or unwound about the drum (32), the elevator car (18) is raised or lowered, respectively.</p>												

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DRUM DRIVE ELEVATOR USING FLAT BELT

TECHNICAL FIELD

- The present invention relates to elevator systems and, more particularly, to a drum drive elevator system that requires minimal installation and operation space and that eliminates the potential of inadvertently driving past the top terminal.

BACKGROUND OF THE INVENTION

- Known drum drive elevator systems typically involve "cotton reel" type drum and lifting rope arrangements where the rope is wound onto the drum with successive turns such that each length of rope is placed adjacent to the prior length to form a single layer of wound rope. Such systems are usually limited to single layer rope winding because of safety and rope life considerations. In situations where the elevator car must travel over a large rise, the length of the drum required to accommodate single layer rope winding becomes impractical. Because of the length of the drum in such instances, large variations in the rope path occur as the rope is wound along the drum. This may cause difficulty in the placement of guidance sheaves and may result in changing direction of forces imposed on the elevator car thereby affecting ride quality.

- In typical elevator systems, lifting force on an elevator car is delivered from a sheave located above the car. Without additional means of control, the lifting force could continue to be delivered until the elevator car impacts either the ceiling of the hoistway or the sheave. Thus, there exists the potential in conventional elevator systems having the drive sheave or drum located overhead that the elevator car may be accidentally driven through the top terminal. Special precautions are ordinarily required to ensure that drive force is disabled when the elevator car moves beyond the top terminal level. In traction elevator systems, for example, a deceleration zone and safety equipment such as a rope brake are required, adding cost and space consumption.

- Conventional drum and traction elevator systems usually require a large machine room to accommodate the overhead machine and components, including safety features. It is desirable to eliminate the need for a large machine room and its associated costs and building structure requirements.

OBJECTS AND SUMMARY OF THE INVENTION

It is an object of the present invention to provide a drum elevator system that requires minimal machine room space. It is a further object to
5 provide a drum elevator system that has inherent safety features to eliminate the potential of driving through the top terminal. These and other inherent objects are achieved by the invention as described below.

The present invention elevator system utilizes a drum and rope system that allows multiple layers of rope winding around the drum. The
10 arrangement eliminates the problems described above associated with rope path variation and ride quality, while increasing the practical limit for rise height. The present invention elevator system also ensures that the lifting force on the elevator car is reduced to zero at a short distance past the upper terminal level, thereby eliminating the over-rise problem described above.
15 This loss of lifting force is inherently controlled by the sizing and spatial arrangement of the drum, car sheaves, a diverter sheave and the fixed hitch point of the belt. In the present invention the vertical positions of the drum and the fixed hitch point define the limit of the highest achievable vertical position of the elevator car. This feature eliminates the need for speed
20 limiting or other safety features.

The present invention elevator system requires only a small machine room that can be located on the top terminal floor, avoiding the need for a separate structure and special building requirements. There is no requirement for hoistway space to accommodate a counterweight, as is required with
25 conventional traction systems.

In another embodiment of the present invention, an elevator system utilizes a single drum drive positioned at the bottom of the hoistway, or in the hoistway pit, and is adapted to simultaneously wind two traction belts. Each traction belt is attached to and supports one side of the elevator car. One end
30 of each belt is attached to the elevator car, and the other end of each belt is attached to the drive drum for selective winding to retract or release belt length, thereby controlling vertical movement of the elevator car. The positioning of the drum drive in the pit eliminates the need for a machine room or external structure for mounting the drive, while allowing sufficient
35 space for the double-wound drum when the elevator car is in a raised position.

These and other advantages are apparent from the description provided below.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a partial, schematic, side cross-sectional view of an elevator system according to the present invention, showing the elevator car near a top position.

Fig. 2 is a view as shown in Fig. 1, in which an elevator car is at the absolute top position.

10 Fig. 3 is a partial, schematic side view of an elevator car assembly according to the present invention.

Fig. 4 is a partial, schematic perspective view of an elevator car assembly according to Fig. 3.

15 Fig. 5 is a partial, schematic perspective view of an elevator system of according to a second embodiment of the present invention.

FIG. 5a is an enlarged, fragmentary view of the drive drum.

FIG. 6 is a sectional view of one of the flat ropes.

DESCRIPTION OF THE PREFERRED EMBODIMENT

20 Referring to Fig. 1, the present invention elevator system (10) includes a drum drive assembly (12), a diverter sheave (14), a belt (16), and an elevator car (18) having two underside sheaves (20, 22). The elevator car (18) and associated sheaves (20, 22) are positioned for vertical movement within a
25 hoistway (24). The belt (16) is fixed at one end to a first hoistway wall (26). The other end of the belt (16) passes through an opening (28) in a second hoistway wall (30) and engages a drum (32) component of the drum drive (12) in a wrap-around fashion. The diverter sheave (14) is mounted in the second hoistway wall (30).

30 The drum drive assembly (12) is mounted on a base (34) that is fixed relative to the hoistway. The assembly (12) includes a conventional motor (not shown) and a drum (32) adapted to selectively rotate in either direction. The belt (16), preferably a flat belt or flat rope, is wound successively around the drum (32). The terms "flat ropes" or "flat belts" as used herein refer to
35 ropes or belts having an aspect ratio greater than one, where the aspect ratio is defined as the ratio of the rope or belt width to thickness. The belt or rope

should be sufficiently thin to enable successive winding around the drum so that a rope or belt of sufficient length to enable a desired range of lift height can be used. Conventional controls are used to activate and direct power to the motor which, in turn, imparts torque to cause the drum (32) to rotate thereby winding or unwinding the belt (16).

In operation, the elevator car (18) can be lowered from the raised position shown in Fig. 1 by activating the motor to turn the drum (32) counterclockwise to unwind the belt (16) from the drum (32). As the belt (16) is let out over the diverter sheave (14) and underneath the two car-mounted sheaves (20, 22), the force of gravity acting on the elevator car (18) forces the car (18) to move downward while being supported by the belt (16). Conventional guide or track means (not shown) are used to guide the car movement as it descends or ascends. The first end of the belt (16) remains fixed to the first hoistway wall (26). When the desired car (18) position is reached, the drum (32) is stopped. In order to raise the elevator car (18), the same procedure is followed with the drum (32) being caused to rotate in the opposite direction.

A safety feature of the present invention for preventing the elevator car (18) from overrunning or from rising higher than the upper terminal is dependent upon the sizing and positioning of the fixed end of the belt (16) and the drum (32). While the preferred embodiment is directed to a drum drive, it is possible to implement the presently described features in a system using a traction drive.

Referring to Fig. 2, with the drum (32) placed at the top floor level and the fixed end of the belt (16) located at approximately top floor level, the elevator car (18) can be driven only up to a point where the bottoms of the car sheaves (20, 22) are level with a plane connecting the top of the diverter sheave (14) and the fixed point of the belt (16). Even with infinite tension on the belt (16) the elevator car (18) cannot travel above this point. Thus, the diameter and placement of the diverter sheave (14), the diameter and placement of the car sheaves (20, 22), and the position of the fixed belt (16) point limit the vertically upward travel of the elevator car (18).

The car sheaves (20, 22) are offset with respect to vertical height for the reasons explained below. As the elevator car (18) travels upward, the center of the first car sheave (20) passes the center of the diverter sheave (14). As a result, the tension necessary to maintain upward travel increases, as the

load of the car (18) formerly supported by the first car sheave (20) is transferred to the second car sheave (22).

As the center of the first car sheave (20) passes the center of the diverter sheave (14), and the tension necessary to maintain upward travel of the car (18) begins to increase, the net lifting force will be reduced in a cosine like manner, reducing from one hundred percent of the belt tension when the center of the first car sheave (20) is level with the center of the diverter sheave (14), to zero when the bottom of the first car sheave (20) is level with the top of the diverter sheave (14). Movement of the second car sheave (22) past the fixed hitch point of the belt (16) has a similar effect on net lifting force from the second car sheave (22), but the net force reduction occurs over a movement of only half the sheave (22) diameter.

Thus, the rate of deceleration of the elevator car (18) is controlled by the diameter and placement of the diverter sheave (14), the diameter and placement of the car sheaves (20, 22), and the placement of the fixed hitch point of the belt (16).

The arrangement of components of the present invention elevator system (10) imposes minimal requirements on the building structure. All vertical forces are supported by the hoistway (24). Horizontal forces from belt tension are supported by the top terminal floor. No special machine or hitch beams are required. The total mass that needs to be transported to, installed in and supported by the building structure is less than half of that associated with a conventional traction elevator system. Only minimal top overrun clearance is necessary, and no overhead machine room is needed. The present invention elevator system can be used in a smaller hoistway space than a traction system that requires room for a counterweight.

The construction of the car (18) and its sheave components used with the preferred embodiment as described herein is described with respect to Figs. 3 and 4. In the side view of Fig. 4 there is disclosed a pair of cantilever supports (36, 38) that support the car (18) from underneath at the car floor (48) and that extend from a pair of vertical frame members (40, 42). Not all of the car walls (44, 46) are shown, nor the roof, in order to allow illustration of other components. The car (18) may be made with a single entrance or with double entrances. The vertical frame members (40, 42) may be provided with conventional safety and guide components (not shown).

The vertical frame members (40, 42) are limited in height so as to not extend above the top of the car (18). The car walls (44, 46), floor (48), and roof are formed from a thin structural material, such as an aluminum sandwich panel, to enable them to be self-supporting. Such construction enables
5 minimum wall thickness with maximum floor area. The drum drive assembly (12) is located on the top floor at the side of the hoistway (24) or in a small machine room (not shown) at the same level as the top floor. In order to ensure that vertical loads are passed directly to the hoistway wall (30), the diverter sheave (14) is positioned in an opening (28) in the wall (30) enabling
10 the diverter sheave (14) to extend slightly into the hoistway (24). The diverter sheave (14) is positioned as closely as possible to the floor level to minimize overrun distance.

The hitch point for the end of the belt (16) is on the wall (26) opposite the drum drive assembly (12). The hitch point is located vertically so that,
15 when the elevator car (18) is at the top floor level, a substantially straight line can be drawn through points connecting the top of the diverter sheave (14), the bottom of each car sheave (20, 22), and the hitch point. This is the maximum vertical position attainable by the car (18).

Because the car (18) is lifted essentially through its center of mass,
20 there are only small loads placed on guides, guide rails, or the car structure except for loads caused by use of safety equipment that may be utilized.

The drum drive assembly (12) is preferably a single unit including a motor, a gearbox, a brake, a drum, a diverter pulley, a drive, a controller and a governor.

25 While the preferred embodiment utilizes a diverter sheave (14) and two car sheaves (20, 22), it is possible to implement a system within the scope of the present invention in which no diverter sheave is used and in which a different number of car sheaves such as, for example, one sheave is used or in which no car sheaves are used. The position of the car sheave or sheaves on
30 the elevator car is not necessarily limited to the bottom of the elevator car and may be, for example, on the top of the elevator car.

A second embodiment of the present invention is directed to the elevator system (200) shown in Fig. 5. The system (200) includes a hoistway (202), an elevator car (204), a drive assembly (206) including a drive drum (208) located at the bottom (210) or in the pit of the hoistway (202), a pair of
35 drive belts (212, 214), a pair of counterweights (216, 218) attached to the

drive belts (212, 214), a pair of suspension sheaves (220, 222), and two sets of diverter pulleys (224, 226). The drive drum (208) receives both belts (212, 214) simultaneously so that they wrap and unwrap over each other. By sharing a single drive drum (208), the two belts (212, 214) are easily
5 synchronized and the space required for the drive assembly (206) is minimal. By positioning the drum (208) below in the hoistway (202), there is sufficient space to accommodate the increased diameter of the drum (208) when the belts (212, 214) are fully wound and the elevator car (204) is in the fully raised position. The diverter pulleys (224, 226) maintain the necessary
10 positioning of the belts (212, 214) to enable simultaneous winding around the same drum (208).

A principal feature of the present invention is the flatness of the ropes used in the above described elevator system. The increase in aspect ratio results in a rope that has an engagement surface, defined by the width
15 dimension "w", that is optimized to distribute the rope pressure. Therefore, the maximum rope pressure is minimized within the rope. In addition, by increasing the aspect ratio relative to a round rope, which has an aspect ratio equal to one, the thickness "t1" of the flat rope (see Fig. 6) may be reduced while maintaining a constant cross-sectional area of the portions of the rope
20 supporting the tension load in the rope.

As shown in Fig. 6, the flat ropes 722 include a plurality of individual load carrying cords 726 encased within a common layer of coating 728. The coating layer 728 separates the individual cords 726 and defines an
25 engagement surface 730. The load carrying cords 726 may be formed from a high-strength, lightweight non-metallic material, such as aramid fibers, or may be formed from a metallic material, such as thin, high-carbon steel fibers. It is desirable to maintain the thickness "d" of the cords 726 as small as possible in order to maximize the flexibility and minimize the stress in the cords 726. Steel fibers having such diameter improve the flexibility of the cords and the
30 rope. By incorporating cords having the weight, strength, durability and, in particular, the flexibility characteristics of such materials into the flat ropes, the maximum rope pressure may be maintained within acceptable limits.

The coating layer 728 is formed from a polyurethane material, preferably a thermoplastic urethane, that is extruded onto and through the
35 plurality of cords 726 in such a manner that each of the individual cords 726 is restrained against longitudinal movement relative to the other cords 726.

Other materials may also be used for the coating layer if they are sufficient to meet the required functions of the coating layer: wear, transmission of loads to the cords and resistance to environmental factors.

- 5 As a result of the configuration of the flat rope 722, the rope pressure may be distributed more uniformly throughout the rope 722. Because of the incorporation of a plurality of small cords 726 into the flat rope elastomer coating layer 728, the pressure on each cord 726 is significantly diminished over prior art ropes. Cord pressure is decreased at least as $n^{-1/2}$, with n being the number of parallel cords in the flat rope, for a given load and wire cross
- 10 section. Therefore, the maximum rope pressure in the flat rope is significantly reduced as compared to a conventionally roped elevator having a similar load carrying capacity.


- While the preferred embodiment of the present invention has been herein described, it is acknowledged that variation of the aforescribed
- 15 embodiment may be undertaken without departing from the scope of what is presently claimed.

I CLAIM :


- 1) An elevator system comprising
an elevator car ;
5 a drum machine ; and
a belt engaged with said elevator car and with said drum
machine, such that said drum machine can be operated to move said
elevator car.
- 10 2) An elevator system according to claim 1, further comprising
at least one belt-engaging sheave attached to said elevator car
to engage said belt.
- 15 3) An elevator system according to claim 1, wherein
said belt has a first end fixed with respect to a hoistway at a
vertical position defining the uppermost position to which said
elevator car can move.
- 20 4) An elevator system according to claim 3, wherein
said drum machine receives a second end of said belt in a
manner such that said belt can be selectively retracted into or released
from said drum machine to effect raising or lowering of said elevator
car.
- 25 5) An elevator system according to claim 2, further comprising
at least one diverter sheave fixed relative to a hoistway and
positioned between said drum machine and said belt.

- 6) An elevator system comprising
an elevator car adapted to travel along a path ;
a drive machine positioned adjacent to said path ;
a rope engaged with said elevator car and with said machine ;
5 a hitch point at which a first end of said rope is fixed, and
wherein the relative locations of the drive machine and hitch point
prevent overtravel of the car.
- 7) An elevator system according to claim 6, wherein
10 said hitch point is located on a wall of a hoistway in which said
elevator car resides.
- 8) An elevator system according to claim 6, further comprising
at least one sheave attached to said elevator car and being
15 adapted to engage said belt so that said elevator car is supported by
said belt through said sheave.
- 9) An elevator system according to claim 6, wherein
said drive machine is a drum drive machine.
20
- 10) An elevator system according to claim 6, wherein
said drive machine is a traction drive machine.
- 11) An elevator system comprising
25 an elevator car ;
a drive assembly including a drive drum ; and
a pair of drive belts, each having one end fixed to said elevator
car and each having the other end fixed to said drive drum, whereby
said elevator car is suspended by said belts and is selectively moved by
30 activating said drive drum.

1/4



2/4






FIG. 3




FIG. 4




FIG. 5




FIG. 5A




FIG. 6

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/03650

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B66B11/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B66B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 910 383 A (FRIEDL VLADIMIR) 7 October 1975 see abstract	1
Y	see figures	2-5,8
A	---	6,11
Y	CONTACTOR: "Electric lifts - A Practical Treatise on their Construction Operation and Maintenance" August 1942, GEORGE NEWNES LIMITED, LONDON XP002103802	2-10
A	see page 23, paragraph 2 see figure 18	1,11
Y	EP 0 688 735 A (KONE OY) 27 December 1995 see abstract; figure 4 ---	6,7,9,10
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"A" document member of the same patent family

Date of the actual completion of the international search

4 June 1999

Date of mailing of the international search report

23/06/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Salvador, D

INTERNATIONAL SEARCH REPORT

Int. Patent Application No.

PCT/US 99/03650

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>DATABASE WPI Section PQ, Week 9020 Derwent Publications Ltd., London, GB; Class Q38, AN 90-153541 XP002103803 & SU 1 518 277 A (BLOKHIN A V) , 30 October 1989 see abstract</p>	11
A	<p>DE 23 33 120 A (VOGEL RUDOLF DR ING) 23 January 1975 see page 5, paragraph 3</p>	1-11
A	<p>DE 25 23 345 A (KONE OY) 11 December 1975</p>	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/03650

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3910383	A	07-10-1975	NONE	
EP 0688735	A	27-12-1995	FI 95689 B AU 693542 B AU 2173595 A BR 9502924 A CA 2152292 A CN 1117938 A DE 29521931 U DE 688735 T EP 0891939 A JP 2777340 B JP 8040676 A	30-11-1995 02-07-1998 11-01-1996 30-01-1996 24-12-1995 06-03-1996 05-11-1998 09-04-1998 20-01-1999 16-07-1998 13-02-1996
DE 2333120	A	23-01-1975	NONE	
DE 2523345	A	11-12-1975	FI 164174 A FR 2275400 A SE 7506063 A	29-11-1975 16-01-1976 01-12-1975